

Power · Precision · Performance

10-100W Single output Plastic DIN rail power supply
-----DP-M Series



3 years
Warranty

☒ Wide Input Voltage Range

- 85~264VAC / 120~370VDC (47~63Hz)
- Suitable for global applications with unstable power grids.

☒ High Efficiency – Up to 88% energy conversion

☒ Ultra-Low Noise – Ripple as low as 80mVp-p

☒ Comprehensive Protection Features

- Short circuit / Overload (Auto-recovery (105%~160% cut-off))/ Overvoltage (120%~140% shutdown with manual reset)

☒ DIN Rail Mounting – Easy installation (TS-35/7.5 or 15)

☒ LED Power Indicator – Visual power-on status.

Selection guide

Power (W)	Available Output Voltages (V)	Max Current (A)
10W	5V, 12V, 15V, 24V	0.42A ~ 2A
20W	5V, 12V, 15V, 24V	0.1A ~ 3A
40W	5V, 12V, 24V, 48V	0.83A ~ 6A
60W	5V, 12V, 24V, 48V	1.25A ~ 10A
100W	12V, 24V, 36V, 48V	2A ~ 7.5A



Industrial-Grade Guide Rail Solutions · Customized for Various Equipment

- Suitable for CNC Machine Tools
- Automated Production Lines
- Precision Instruments

High-Precision Enclosure DIN Rails

- Traditional guide rails: Prone to wear, large precision deviation, high maintenance costs
- Our product: Wear-resistant coating technology, micron-level precision, maintenance-free design

GUANGZHOU AMCHARD-POWER ELECTRONIC CO., LTD.

Mail: info@amchard-power.com

Teams: 15764145@qq.com

Website: www.amchard-power.com



Website

AMCHARD