


Features

1. Wide operating temperature range: -40°C to +105°C
2. Up to 85% efficiency
3. No load current as low as 5mA
4. Ripple as low as 30mVp-p
5. Sustainable short-circuit protection
6. Isolation:3000VDC
7. Fixed voltage input, Output 1W, Isolated, Non stabilized voltage, Positive and negative dual output, SMD package.



3 years
Warranty

Model Numbering

AMExxxxXT-1WR3



Selection Guide

Product model	Input Voltage Standard value(range)	Output Voltage	Output Current (mA) (Max./Min.)	Efficiency % (Min./Typ.)	Maximum capacitive load (μF)
AME0303XT-1WR3	3.3VDC (2.97-3.63)	±3.3	±152/±15	70/74	1200
AME0305XT-1WR3		±5	±100/±10	78/82	1200
AME0309XT-1WR3		±9	±56/±6	78/83	470
AME0312XT-1WR3		±12	±42/±5	78/83	220
AME0315XT-1WR3		±15	±34/±4	78/83	220
AME0324XT-1WR3		±24	±21/±3	80/85	100

Product model	Input Voltage Standard value(range)	Output Voltage	Output Current (mA) (Max./Min.)	Efficiency % (Min./Typ.)	Maximum capacitive load (μ F)
AME0503XT-1WR3	5VDC (4.5-5.5)	± 3.3	$\pm 152/\pm 15$	70/74	1200
AME0505XT-1WR3		± 5	$\pm 100/\pm 10$	78/82	1200
AME0509XT-1WR3		± 9	$\pm 56/\pm 6$	78/83	470
AME0512XT-1WR3		± 12	$\pm 42/\pm 5$	78/83	220
AME0515XT-1WR3		± 15	$\pm 34/\pm 4$	78/83	220
AME0524XT-1WR3		± 24	$\pm 21/\pm 3$	80/85	100
AME0903XT-1WR3	9VDC (8.1-9.9)	± 3.3	$\pm 152/\pm 15$	70/74	1200
AME0905XT-1WR3		± 5	$\pm 100/\pm 10$	78/82	1200
AME0909XT-1WR3		± 9	$\pm 56/\pm 6$	78/83	470
AME0912XT-1WR3		± 12	$\pm 42/\pm 5$	78/83	220
AME0915XT-1WR3		± 15	$\pm 34/\pm 4$	78/83	220
AME0924XT-1WR3		± 24	$\pm 21/\pm 3$	80/85	100
AME1203XT-1WR3	12VDC (10.8-13.2)	± 3.3	$\pm 152/\pm 15$	70/74	1200
AME1205XT-1WR3		± 5	$\pm 100/\pm 10$	78/82	1200
AME1209XT-1WR3		± 9	$\pm 56/\pm 6$	78/83	470
AME1212XT-1WR3		± 12	$\pm 42/\pm 5$	78/83	220
AME1215XT-1WR3		± 15	$\pm 34/\pm 4$	78/83	220
AME1224XT-1WR3		± 24	$\pm 21/\pm 3$	80/85	100
AME1503XT-1WR3	15VDC (13.5-16.5)	± 3.3	$\pm 152/\pm 15$	70/74	1200
AME1505XT-1WR3		± 5	$\pm 100/\pm 10$	78/82	1200
AME1509XT-1WR3		± 9	$\pm 56/\pm 6$	78/83	470
AME1512XT-1WR3		± 12	$\pm 42/\pm 5$	78/83	220
AME1515XT-1WR3		± 15	$\pm 34/\pm 4$	78/83	220
AME1524XT-1WR3		± 24	$\pm 21/\pm 3$	80/85	100
AME2403XT-1WR3	24VDC (21.6-26.4)	± 3.3	$\pm 152/\pm 15$	70/74	1200
AME2405XT-1WR3		± 5	$\pm 100/\pm 10$	78/82	1200
AME2409XT-1WR3		± 9	$\pm 56/\pm 6$	78/83	470
AME2412XT-1WR3		± 12	$\pm 42/\pm 5$	78/83	220
AME2415XT-1WR3		± 15	$\pm 34/\pm 4$	78/83	220
AME2424XT-1WR3		± 24	$\pm 21/\pm 3$	80/85	100

Parameter	Conditions		Min.	Typ.	Max.	Units
Input current (Rated Load)	Nominal voltage input@3.3VDC	3.3VDC Output	--	384	405	mA
		5VDC/7.2VDC Output	--	370	389	mA
		9VDC/12VDC Output	--	365	389	mA
		15VDC/24VDC Output	--	350	389	mA
	Nominal voltage input@5VDC	3.3VDC Output	--	271	286	mA
		5VDC/7.2VDC Output	--	244	257	mA
		9VDC/12VDC Output	--	241	254	mA
		15VDC/24VDC Output	--	241	254	mA
	Nominal voltage input@12VDC	3.3VDC Output	--	112	118	mA
		5VDC/7.2VDC Output	--	105	110	mA
		9VDC/12VDC Output	--	104	110	mA
		15VDC/24VDC Output	--	103	110	mA
	Nominal voltage input@15VDC	3.3VDC Output	--	84	89	mA
		5VDC/7.2VDC Output	--	84	89	mA
		9VDC/12VDC Output	--	83	89	mA
		15VDC/24VDC Output	--	83	88	mA
	Nominal voltage input@24VDC	3.3VDC Output	--	56	61	mA
		5VDC/7.2VDC Output	--	53	58	mA
		9VDC/12VDC Output	--	53	58	mA
		15VDC/24VDC Output	--	52	58	mA
Input current (No-load)			--	5	20	mA
Reflected ripple current			3	15	20	mA
Input impulse voltage	1sec. max.	3.3VDC/5VDC Input	-0.7	--	9	VDC
		9VDC Input	-0.7	--	12	VDC
		12VDC Input	-0.7	--	18	VDC
		15VDC Input	-0.7	--	21	VDC
		24VDC Input	-0.7	--	30	VDC
Input filter	Capacitive filtering					
Remarks: This product does not support hot plug						

Output Characteristic

Parameter	Conditions		Min.	Typ.	Max.	Units
Output voltage accuracy			See Figure 3 (envelope curve)			
Linear regulation rate	Input voltage variation+/- 1%	3.3VDC Output	--	--	+/-1.5	%
		Other outputs	--	--	+/-1.2	%
Load regulation rate	10% to 100% load	3.3VDC Output	--	15	20	%
		5VDC Output	--	10	15	%
		9VDC Output	--	8	10	%
		12VDC Output	--	7	10	%
		15VDC Output	--	6	10	%
		24VDC Output	--	5	10	%
Ripple & Noise	20MHz bandwidth		--	30	100	mVp-p
Temperature drift coefficient	100% load		--	+/-0.03	--	%/°C
Short circuit protection	Sustainable, Self-healing					
Note: The testing method for ripple and noise is the parallel line testing method.						

General Characteristics/

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation voltage	Input-output, Test time 1 minute, Leakage current less than 1 mA	3000	--	--	VDC
Insulation resistance	Input-output, Insulation voltage 500VDC	1000	--	--	MΩ
Isolation capacitance	Input-output, 100KHz/0.1V	--	20	50	pF
Working temperature	Temperature ≥ 85 °C for derating (See Figure 4)	-40	--	+105	°C
Storage temperature		-55	--	+125	°C
Storage humidity	Non condensing	--	--	95	%RH

Parameter	Conditions	Min.	Typ.	Max.	Units
Housing temperature rise during operation	Ta=25 °C, Nominal input, Full output	- -	15	25	°C
Soldering temperature resistance of pins	The distance from the welding spot to the shell is 1.5mm, 10 seconds	- -	- -	300	°C
	REFLOW:Peak temperature Tc ≤ 245 °C, maximum time above 217 °C for 60 seconds.	- -	- -	245	°C
Switching frequency	Full load, Nominal input voltage	- -	270	- -	kHz
Mean time between failures 【MTBF】	MIL-HDBK-217F@25°C	3500	- -	- -	kHours

Physical Characteristics

Parameter/参数	Content/内容
Housing material	Black flame retardant and heat-resistant plastic (UL94V-0)
Overall dimensions	15.24 x 11.40 x 7.25mm (Length * Width * Height)
Weight	1.2g(Typ.)
Cooling mode	Natural air cooling

EMC Characteristics

Parameter	Category	Content
EMI	Conductive disturbance	CISPR32/EN55032 CLASS B (The recommended circuit is shown in Figure 2)
	Radiation disturbance	CISPR32/EN55032 CLASS B (The recommended circuit is shown in Figure 2)
EMS	Electrostatic discharge	IEC/EN61000-4-2 Contact ±4KV perf. Criteria B

Circuit Design and Application




Figure 1: Application circuit

Table 1:
Recommended Capacitive Load Values

Vin(VDC)	Cin(μF)	Vo(VDC)	Cout(μF)
Nominal voltage	1-10	Nominal voltage	2.2-22




Figure 2: EMC Typical Recommended Circuits

Table 2:
Recommended Circuit Parameter Values

Category	Component	Value
EMI	C1	4.7μF /50V
	C2	4.7μF /50V
	C3,C4	2.2-22μF /50V
	CY	270pF/2kV
	LDM	6.8μH

1. Typical application: If further reduction of input and output ripple is required, a capacitor filter network can be connected at the input and output ends. The application circuit is shown in Figure 1. However, suitable filter capacitors should be selected. If the capacitance is too large, it may cause overcurrent or poor startup of the power supply. For each output, while ensuring safe and reliable operation, the recommended capacitance load values are shown in Table 1.
2. EMC requirements: For situations with high EMC requirements, a typical EMC recommended circuit is shown in Figure 2.
3. Input requirements: Ensure that the fluctuation range of the input voltage does not exceed the upper and lower limits of the input voltage specified in this data sheet, and the input power must be greater than the output power specified in this data sheet. For situations with a 24V input voltage, it is recommended to connect a TVS tube between the positive and negative input pins for protection (recommended parameters for TVS tubes: 30V, bidirectional, SOD-123 packaging).
4. Output load requirements: Try to avoid using it without load as much as possible; When the actual power of the load is less than 10% of the rated output power in this data sheet, or when it needs to be used in no-load situations, it is recommended to connect a load resistor externally at the output end. The load resistor can be calculated according to 5-10% of the rated power in this data sheet. The calculation formula for the load resistor value is $R_L = U_{out}^2 / (P_{out} * 10\%)$.
5. Overload protection: Under normal working conditions, the output circuit of this product has no protection function for overload situations. The simplest method is to connect a self recovery fuse in series at the input end, or add a circuit breaker outside the circuit; Or during design and selection, the actual power of the circuit should be around 60-80% of the rated power in this data sheet.

Product Characteristic Curve




Figure 3: Voltage tolerance envelope




Figure 4: Temperature Derating Curve




Figure 5: Efficiency VS Output Load (Nominal Voltage Input)




Figure 6: Efficiency VS Input Voltage (100% Load)

Overall Dimensions and Pin Functions




Figure 7: Overall dimensions

Table 3: Pin Function Table

Pin	Function
1	GND
2	Vin
4	0V
5	-Vo
7	+Vo
10	NC

Note:
Dimensions in mm
Terminal diameter tolerance: ± 0.10
Undeclared tolerance: ± 0.50

Notes & Instructions

1. The input voltage shall not exceed the specified range value, otherwise permanent and unrecoverable damage may be caused;
2. Unless otherwise specified, the parameters in this manual are measured at 25 °C, 40%~75% humidity, input nominal voltage and output pure resistance mode under full load;
3. All index test methods are based on the company's enterprise standards.
4. The copyright and the final interpretation right of the product belong to AMCHARD.

DONGGUAN AMCHARD-POWER TECHNOLOGY CO., LTD.

www.amchard-power.com

Mail: info@amchard-power.com